

CAM 8800 SERIES

MOBILE SURVEILLANCE IP CCTV CAMERAS

GAMETRON

CAM 8899 IPID

FEATURES

H.264 video format,
G711U audio compression
Video resolution 1920 x 1080,
Effective pixels: 2MP, 25fps, 128kbps ~ 8Mbps
VBS & CBS manual switching
10M/100M, RJ45 port;
HTTP, TCP/IP, ICMP,RTSP, RTP, UDP, RTCP, SMTP, DHCP, DNS,
PPPoE internet protocol;
Contrast, brightness, saturation, sharpness adjustment
Automatic exposure control, gain control, white balance
Support ONVIF, POE



rear view IR camera

SPECIFICATIONS

Image sensor	COLOR 1/4"CMOS
Resolution	PAL/ NTSC:1280(H)×720(V)
Horizontal Resolution	Color 720P (Black & White 720P)
Min. illumination	Color 0. 1Lux @(F1.2,AGC ON),0 LUX with IR off Black & White 0.01 Lux @ (F1.2,AGC ON),0 LUX with IR on
Standard/ Frames	PAL (25FPS) /NTSC (30 FPS) Optional
Video compression	H.264/MJPEG
Shutter speed	Auto expose,1/50S to 1/100000S
Lens	3MP HD 3.6mm @ F2.0(2.8~12 mm optional)
FOV	Horizontal:45°; Vertical:0°~90°
Day & night mode	Dual ICR auto color/night
Synchronization system	Inter-sync
Video output	1Ch, meet ONVIF protocol (Connector: RJ45 and 6pins aviation optional)
Video output rates	32 Kbps~8Mbps
SNR	>52db
Protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/ONVIF
Audio	-
Color	Black
Operating temperature	10°C~60°C
Humidity	<90%(no condensation)
Power supply	DC12V±10%
Power consumption	<5W
Video output cable length	40cm
Ingress protection	IP66
IR range	10 Meters
Dimensions(mm)	80 x 77 x 70 (Lx W x H)
Package dimension	125x80x65mm
Net/gross	340 g /341g