

CAM 8800 SERIES

MOBILE SURVEILLANCE IP CCTV CAMERAS

CAMETRON

CAM 8829 IPID

FEATURES

H.264 video format,G711U audio compression
Video resolution 1920 x 1080
Effective pixels 2MP, 25fps, 128kbps ~ 8Mbps
VBS/CBS manual switching
10M/100M, RJ45 port
Support HTTP, TCP/IP, ICMP,RTSP, RTP, UDP,
RTCP, SMTP, DHCP, DNS, PPPoE
Contrast, brightness, saturation, sharpness adjustment
Automatic exposure control, gain control, white balance
Support ONVIF, POE



side mount infra red IR camera

SEPCIFICATIONS

Image sensor	COLOR 1/4"CMOS
Resolution	PAL/ NTSC:1280(H)×720(V)
Horizontal Resolution	Color 720P(Black720P)
Min.illumination	Color 0. 1Lux @(F1.2,AGC ON),0 LUX with IR off Black & white 0.01 Lux @ (F1.2,AGC ON),0 LUX with IR on
Signal system/ Frames	PAL (25FPS) /NTSC (30 FPS) Optional
Video compression	H.264/MJPEG
Shutter speed	Auto expose,1/50S to 1/100000S
Lens	3MP HD 2.8mm
FOV	Horizontal:0°~60°; Vertical:0°~60°;Rotation:0°~355°
Day / Night mode	Dual ICR auto color/night
Synchronization system	Inter-sync
Video output	1CH,meet ONVIF protocol (Connector: RJ45 and 6pins aviation optional)
Video compression rates	32 Kbps~8Mbps
SNR	>52db
Mount protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/ONVIF
Audio	-
Color	Black
Operating temperature	-10°C~60°C,
Humidity:	<90%(no condensation)
Power supply	DC12V±10%
Power consumption	< 4W
Video cable length	40cm
Ingress protection	Waterproof IP65,IP66 customizable
IR range	10 Meters
Dimensions(mm)	85mm x 62mm x 57mm (LWH)
Weight Net/gross	163 g /219g