

IP Video Surveillance Systems 10 Channel H.265 4K Resolution NVR

CAMETRON
NETWORK VIDEO RECORDERS

CT 601001 CDK

Introduction

CAMETRON Network Video recorders are the perfect choice for security professionals owing to stability, reliability, easy installation and highest level of protection. These NVR's support the Cametron series of network cameras & all the major brands of IP CCTV cameras & the proprietary protocol.

CAMETRON NVR's make it very easy to manage, access and control the associated IP CCTV systems with state of art features like search of videos based on time & date, System integration with access controls, fire alarm systems, electronic article surveillance

The series supports automatic network replenishment and uses dual Gigabit network. The video content analysis features makes the device series versatile tool for the perimeter & tripwire thereby ensuring the highest level of security



SALIENT FEATURES

- H.265 Video codec
- Input 10 ch 4K, (6,5,4,3)MP,1080P,720P,4CIF
- Display 10 ch 4K, (6,5,4, 3)MP,1080P,720P,4CIF,D1
- Playback 1ch 4K (6,5,4)MP,2ch 3MP,4ch(1080P,720P,4CIF)
- Automatic Network Replenishment
- 4K Recording resolution
- Video Output HDMI x 1, VGA x 1, 4K any source
- Hard disk SATA x 1 (6 TB total)
- Hard disk Quota & group management
- Dual Gigabit network Interface
- USB x 2, RJ 45 (10M/100M)
- Compatible with Observer VMS
- Smartphone Applications SmartCam
- USB x 2, RJ 45 (10M/100M)
- CTSERVER™ VMS (free till 200 Channels)
- CTSERVER™ PRO VMS (1000 Channels)



CAMETRON NVR comes with the bundle software package CTSERVER™ for live viewing of 100 IP CCTV cameras on a single screen. and with the feature of connection upto 200 channels. The software free version CTSERVER basic supports the playback unto nine channels, with all universal controls like PTZ, Alarm controls, nested maps using BMP & JPEG images, video walls.

CTSERVER™ VMS supports unto 100 split screens with switch mode features based on cameras, groups, channels, manual etc.

The unit comes with the featured support for SAN & video search unto three index levels based on storage location, recording host, group name, channel name & file type. The CTSERVER™ software supports the device detection status & intelligent video analytics like tripwire etc.



IP Video Surveillance Systems

10 Channel H.265 4K Resolution NVR

CT 601001 CDK SPECIFICATIONS

VIDEO / AUDIO (input)

Input	10 ch
Audio	-

VIDEO / AUDIO (output)

HDMI	Output	1 ch
	Resolution	3840x2160,2560x1600, 1920x1080, 1280x720, 800x600,1024x768, 1366x768,1440x900,1280x800
VGA	Output	1 ch
	Resolution	1920 x 1080, 1280 x 720, 800 x 600, 1024 x 768, 1366 x 768,1440 x 900, 1280x800
	Mode	Self adaptive resolution & adjustable output
Frame Rate		Mainstream PAL 25fps / NTSC 30fps Substream PAL 25fps /NTSC 30fps
I-frame record		Available
Recording Resolution		4K,6MP,5MP,4MP,QSXGA,3MP,1080P, UXGA, 720P, VGA,4CIF,DCIF, 2CIF, CIF,QCIF
Playback (Sync)		1 Ch (4K, 6MP, 5MP, 4MP) 2ch 3MP, 4ch (1080P, 720P, 4CIF)
Audio		-

INTELLIGENT

NAS	Yes	
Protocol for NAS	NFS supports manual backup only	
Plug & Play	Yes for CAMETRON series	
Corridor Mode	Yes (16:9 ~ 9:16) only for CAMETRON IP CCTV Camera series	
Video Analytics(VCA)	10 Ch Cametron IP CCTV camera for selected Models	
VCA Process	Tripwire, Perimeter	
Smart Search	VCA videos, all cametron cameras	
	Trigger	Manual, timing, motion detection, port alarm, VCA alarm, video occlusion
	Smart	Set recording bit rate for different time
Recording	Alarm	Pre alarm default 10s(5/10/15/60s Optional) , Post alarm default 10s(0/15/30/60/600s optional)
	Format	SDV, export MP4 in H.264
	Encryption	Yes
	Tags	Yes

COMPLIANCE & CERTIFICATIONS

CE	Yes
FCC	Yes
RoHS	Yes
Onvif	Yes (S, G)

NETWORK

Bandwidth (in/out)	40 Mbps / 40 Mbps
Remote users	16 Users unto 48ch videos at once
Browser	IE8, IE9, IE10, IE11, Chrome 30, Firefox 24
Mobile software	P2P & DDNS for Smartphones
Internet Protocol	TCP, UDP, http, Multicast, UPnP, DHCP, DDNS, NFS, NTP, https, RTSP, SADP active on alarm
Email	Bandwidth display, Flow monitor, Capture package
Intelligent	

INTERFACE

Network	1 x RJ-45 10/100/1000Mbps Self-adaptive Ethernet Interfaces
USB Interface	1 x USB2.0, 1 x USB 3.0
Alarm In	0
Alarm Out	1

DECODING

Live view	4K, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF,DCIF, 2CIF, CIF, QCIF
Display	4K, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, VGA, 4CIF,DCIF, 2CIF, CIF, QCIF
Sync playback	1ch 4K,6MP,5MP,4MP 2ch 3MP, 4ch 1080P,720P,4CIF
Split screen	1, 4, 6, 8, 9, 10
e-Zoom	Yes

STORAGE

Hard disk	SATA x 1 (6 TB)
File system	NTFS
Management	HDD Group, Quota,record days costumization
e SATA	-

GENERAL

Language	English, Spanish, Korean, Italian,Turkish, French, Thai, Russian, Polish
Power supply	100 ~ 240V AC, 6.3A, 50 ~ 60 Hz
Power consumption	≤ 80W without HDD
Temperature	-10 °C ~ +55 °C (+14 °F~ + 131 °F)
Humidity	10 % ~ 90 %
Chassis	19" Rack Mount 2U Chassis
Dimensions(mm)	44 x 255 x 231 mm
Weight	Without HDD 0.8 Kg Gross 1.4 Kg

VMS

Ctserver 32	32 Channel VMS *
Ctserver 64	64 Channel VMS *
Ctserver 128	128 Channel VMS *
Ctserver E	256 Channel VMS #
Ctserver P	256+ Channels #
Ctserver™	VMS 200 Channels #
Ctserver™ PRO	VMS 1000 Channels #

free version VMS *
paid version #

Ctserver is the trademark associated with the Cametron for softwares & related applications
specifications subject to change without prior notice**

IP Video Surveillance Systems 10 Channel H.265 4K Resolution NVR



CT 601001 CDK

ACCESSORIES, SOFTWARES & AFFILIATIONS

SOFTWARES

Ctserver 32	32 Channel VMS basic Software Package
Ctserver 64	64 Channel VMS basic Software Package
Ctserver 128	128 Channel VMS basic Software Package
Ctserver E	256 Channel VMS entry Software Package
Ctserver P	256+ Channels VMS professional Software Package



COMPLIANCE



AFFILIATION



Ordering Information

CT 601001 CDK 10 Channel NVR, H.265 Codec, 1 SATA HDD port,

Registered Office

71-75 Shelton Street, Covent Garden, London, WC2H 9JQ, United Kingdom

Website : www.cametron.com , Email : sales@cametron.com

Company No. : 10039369, Registered in England & Wales, United Kingdom.

CAMETRON, CAMETRON trademark and logo, CTSERVER & logo are the registered trademarks of CAMETRON COMMUNICATIONS (EUROPE) LIMITED, registered and pending in various countries. All brand names are registered trademarks of their respective owners, and are used with permission or as allowed under applicable laws.

