

CAM 8800 SERIES

MOBILE SURVEILLANCE IP CCTV CAMERAS

CAMETRON

CAM 8817 IPID

FEATURES

H.264 video format
G711U audio compression
Video resolution:1920 x 1080
Effective pixels: 2MP, 25fps, 128kbps ~ 8Mbps VBS & CBS,
Manual switching
10M/100M, RJ45 port
HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, DHCP, DNS,
PPPoE internet protocol;
Support for contrast, brightness, saturation, sharpness adjustment
Automatic exposure control, gain control, white balance;
Support ONVIF, POE



indoor universal mount infra red IR camera

SEPCIFICATIONS

| | |
|---|--|
| Image sensor | COLOR 1/4"CMOS |
| Resolution | PAL/ NTSC:1280(H)×720(V) |
| Horizontal Resolution | Color 720P(Black720P) |
| Min.illumination | Color 0.1Lux @(F1.2,AGC ON),0 LUX with IR off Black & white 0.01 Lux @ (F1.2,AGC ON),0 LUX with IR on |
| Signal system / Frames | PAL (25FPS) /NTSC (30 FPS) Optional |
| Video compression | H.264/MJPEG |
| Shutter speed | Auto expose,1/50S to 1/100000S |
| Lens | 3MP HD 2.8mm |
| FOV | Horizontal:0°~60°; Vertical:0°~60°;Rotation:0°~355° |
| Day and night mode synchronization system | Dual ICR auto color/night Inter-sync |
| Video output | 1CH,meet ONVIF protocol (Connector: RJ45 and 6pins aviation optional) |
| Video output rates | 32 Kbps~8Mbps |
| SN | > 52db |
| Protocol | RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/ONVIF |
| Audio | built in |
| Color | Black |
| Operating temperature | -10°C~60°C, humidity: |
| Humidity | <90%(no condensation) |
| Power supply | DC12V±10% |
| Power consumption | < 4W |
| Video output cable length | 40cm |
| Ingress protection | Waterproof IP65,IP66 customizable |
| IR range | 10 Meters |
| Dimensions(mm) | 89mm (L) x 77mm (W) x 63mm (H) |
| Net/gross weight | 291g / 338g |